



## Analogue radios

Handheld and mobile radios from Hytera

Hytera's HYT radios for licence-free and licensed analogue communication offer every user a high level of added value. Their robust, compact construction, their useful functionality and their high reliability ensure trouble-free communication, irrespective of whether for professional, personal or leisure use.

Whether it's communication across a construction site, office facility, or perhaps a restaurant and hotel, with HYT analogue radios from Hytera, you can increase the productivity and efficiency of your staff.

**HYT**  
Two-way Radio

# Radio

## TC-446S

### PMR446 handheld radio

The TC-446S licence-free radio combines modern analogue technologies with user-friendly design to boost your productivity.

Thanks to its compact form and light weight, this robust two-way radio is ideally suited for use in facility management, catering and hospitality, production and manufacturing, retail, education and construction.



### Highlights

#### Licence-free two-way radio

The TC-446S is a PMR446 radio and can therefore be used straight out of the box without the need to acquire a radio licence.

#### Longer battery life and energy-saving functions

With a standard battery the TC-446S achieves a battery life that can easily outlast a shift, whilst the optional high capacity battery can last up to 24 hours from a single charge, on a duty cycle of 5-5-90. The programmable energy-saving function activates itself if the two-way radio has not been used for 10 seconds.

#### CTCSS/CDCSS signaling

38 different CTCSS and 61 different CDCSS sub-audio tones deliver a quick and user-friendly direct call, group call and remote control.

#### Time-out timer

The TC-446S features a time-out timer to avoid inadvertent continuous operation.

### Functions

- Monitor function
- CTCSS/CDCSS and hum and noise
- VOX
- Channel scan
- Energy saving mode
- Warning tone for low battery charge state
- Busy channel lockout
- Time-out timer (TOT)
- Programmable via PC
- Line-connected "cloning" function for transferring settings to another two-way radio
- Selectable squelch levels



## Technical Data

General data	
Frequency range	446.00625 MHz to 446.09375 MHz
Channel capacity	16
Channel spacing	12.5 kHz
Operating voltage	7.4 V
Standard battery	1300 mAh (lithium-ion battery)
Frequency stability	± 2.5 ppm
Operating temperature range	-25 °C to +60 °C
Dimensions (H × W × D) (with standard battery, without antenna)	113 × 54 × 35 mm
Weight (with antenna and standard battery)	270 g
Shock and vibration resistance	MIL-STD -810 C/D/E/F
Dust and water protection	IP54

Transmitter	
Transmitting power	0.5 W
Modulation	8 K0F3E
Interfering signals and harmonics	≤ -36 dBm (< 1 GHz) ≤ -30 dBm (> 1 GHz)
Hum and noise	≤ -38 dB
Nominal audio distortion	≤ 5 %

Receiver	
Sensitivity	≤ 0.282 μV
Adjacent channel selectivity	≥ 60 dB
Intermodulation	≥ 60 dB
Spurious response rejection	≥ 70 dB
Hum and noise	≥ 40 dB
Nominal audio power output	800 mW
Nominal audio distortion	≤ 5 % (800 mW)

All technical information was determined at the factory and in accordance with the corresponding standards. Subject to change on the basis of continuous development.

## In the box

		
Lithium-ion battery 1300 mAh BL1301	Belt clip BC12	Charger CH10L19
		
Wrist strap RO03	Switching power adapter for charger PS1044	

## Optional accessories

		
Carrying bag with belt strap NCN001	Lithium-ion battery (1650mAh) BL1719	Programming cable (USB) PC26
		
Remote speaker microphone (IP55) SM08M3	Concealed headset EAM12	Earbuds with D-piece and microphone EHM15

The illustrations are for reference purposes only. The products might differ from these illustrations.



Your Hytera partner:



Further information can be found at:

[www.hytera.co.uk](http://www.hytera.co.uk)

Keep up to date with Hytera on social media.



### Hytera Communications Corporation Limited

**Address:** Hytera Communications (UK) Co. Ltd.

Hytera House, 939 Yeovil Road, Slough, Berkshire. SL1 4NH, UK.

**Tel:** +44 (0) 1753 826 120 **Fax:** +44 (0) 1753 826 121

**www.hytera.co.uk** **info@hyterauk.co.uk**



Hytera reserves the right to modify the product design and the specifications. In case of a printing error, Hytera does not accept any liability. All specifications are subject to change without notice.

Encryption features are optional and have to be configured separately. They are also subject to European export regulations.

**HYT** Hytera are registered trademarks of Hytera Communications Corp. Ltd. © 2017 Hytera Communication Corp., Ltd. All rights reserved.